AURO

	0000	High-grade lime filler		
√ers	sion 3.1	Revision date 08-Jul-2021	Print date 08-Jul-202	
SE	CTION 1: Identification	n of the substance/mixture and of the company/undertaking		
1.1	Product identifier			
	Trade name/designation	on		
	3420000	High-grade lime filler		
1.2	2 Relevant identified uses of the substance or mixture and uses advised against			
	Relevant identified uses			
ŧ	Matt coatings for interior walls and ceilings			
1.3	Details of the supplier of the safety data sheet			
	Supplier AURO Pflanzenchemie Alte Frankfurter Straße 38122 Braunschweig Deutschland	211 Telephone: +49 531 28141-0 Telefax: +49 531 28141-72 E-mail: info@auro.de Website: www.auro.de		
	Department responsib			
	E-mail (competent perso			
1.4	Emergency telephone n Emergency telephone n Only available during of	umber +44 1544388535		
SE	CTION 2: Hazards ider			
 2.1				
2.1	Classification of the substance or mixture			
*	Classification according to Regulation (EC) No 1272/2008 [CLP] The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Eye Dam. 1; Serious eye damage/eye irritation; H318 Causes serious eye damage. STOT SE 3 Irritation to respiratory tract; STOT-single exposure; H335 May cause respiratory irritation. Skin Irrit. 2; Skin corrosion/irritation; H315 Causes skin irritation.			
2.2	Label elements			
	Labelling according to Regulation (EC) No. 1272/2008 [CLP]			
	Hazard pictograms			
	GHS05 GHS07 Signal word			
	Danger			
	Hazard statements			
	H318	Causes serious eye damage.		
*	H335 H315	May cause respiratory irritation. Causes skin irritation.		
ť	Precautionary statements			
	P101 P102 P271 P280 P305 + P351 + P338	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove o	ontact lenses, if present	
	P310	and easy to do. Continue rinsing. Immediately call a POISON CENTER.		

- P310Immediately call a POISON CENTER.P403 + P233Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.



3420000 Version 3.1 High-grade lime filler Revision date 08-Jul-2021

Print date 08-Jul-2021

P501

Dispose of contents/container to industrial incineration plant.

Hazard components for labelling

Calcium dihydroxide

Supplemental hazard information

not applicable

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients.

3.2 Mixtures

Description

Hazardous ingredients

Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
	25,0 < 35,0
)	REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]

Remark

Full text of H- and EUH-statements: see section 16.Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

4.3



3420000High-grade lime fillerVersion 3.1Revision date 08-Jul-2021

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

* Take up mechanically, placing in appropriate containers for disposal.

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
1305-62-0	Calcium dihydroxide	WEL	5 / - (-) mg/m³
1305-62-0	Calcium dihydroxide	WEL	1 / 4 (-) mg/m³

3420000	
Version 3.1	

High-grade lime filler Revision date 08-Jul-2021

Print date 08-Jul-2021

Additional information

Long-term: Long-term occupational exposure limit value short-term: short-term occupational exposure limit value

Biological limit values

No data available

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber) Thickness of the glove material >= 0,4 mm Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

*	Physical state	solid
	Colour	refer to label
	Safety characteristics	
	Odour	characteristic
	Odour threshold	not determined
*	рН	not determined
	Melting point/freezing point	not determined
	Initial boiling point and boiling range	not determined
	Flash point	not determined
	Evaporation rate at 20°C	not determined
	Burning time	not applicable
	Lower explosion limit at 20°C	not determined
	Upper explosion limit at 20°C	not determined
	Vapour pressure at 20°C	not determined
	Density at 20°C	2,491 kg/l
	Water solubility at 20°C	practically insoluble
	Partition coefficient: n-octanol/water	see section 12



3420000 Version 3.1	High-grade lime filler Revision date 08-Jul-2021	Print date 08-Jul-2021
Ignition temperature in °C	not determined	
Decomposition temperature	not determined	
Viscosity	not determined	
Explosive properties	not relevant	
Oxidising properties	not relevant	
9.2 Other information		

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Calcium dihydroxide

LD50: oral (Rat): > 2.000 mg/kg

LD50: oral (Rat): > 2.000 mg/kg

Skin corrosion/irritation

* Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the

3420000 High-grade lime filler Version 3.1 Revision date 08-Jul-2021 aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage. **SECTION 12: Ecological information** 12.1 Toxicity Based on available data, the classification criteria are not met. Acute (short-term) fish toxicity Calcium dihydroxide LC50: (Oncorhynchus mykiss (Rainbow trout)): = 50,6 mg/L (96 h) Method: OECD 203 Acute (short-term) toxicity to algae and cyanobacteria Calcium dihydroxide EC50 (Pseudokirchneriella subcapitata): = 184,57 mg/L (72 h) Method: OECD 201 Calcium dihvdroxide EC10 (Pseudokirchneriella subcapitata): = 79,22 mg/L (72 h) Method: OECD 201 Acute (short-term) toxicity to crustacea Calcium dihydroxide EC50 (Daphnia magna (Big water flea)): = 49,1 mg/L (48 h) Method: OECD 202 Calcium dihydroxide NOEC (Daphnia magna (Big water flea)): = 33,3 mg/L (48 h) Method: OECD 202 12.2 Persistence and degradability No information available. 12.3 Bioaccumulative potential No information available. 12.4 Mobility in soil No information available. 12.5 Results of PBT and vPvB assessment The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. 12.6 Other adverse effects No information available **SECTION 13: Disposal considerations** 13.1 Waste treatment methods Product/Packaging disposal Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Waste codes/waste designations according to EWC/AVV

080120 - aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number

not applicable

14.2 UN proper shipping name

Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

Sea transport (IMDG)

Print date 08-Jul-2021



3420000 Version 3.1	High-grade lime filler Revision date 08-Jul-2021	Print date 08-Jul-20		
	n sense of these transport regulations.			
Air transport (ICAO				
• •	n sense of these transport regulations.			
4.3 Transport hazard c				
not applicable				
4.4 Packing group				
not applicable				
4.5 Environmental haza	ards			
Land transport (ADR	/RID) not applicable			
Sea transport (IMDG) not applicable			
6 Special precautions	s for user			
Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do i case of an accident or leakage. Advices on safe handling: see parts 6 - 8				
-	ccording to Annex II of Marpol and the IBC Code			
•	according to IBC Code.			
4.8 Additional informat	ion			
Land transport (AD	R/RID)			
not applicable				
Sea transport (IMD	G)			
not applicable				
Air transport (ICAO	-TI / IATA-DGR)			
not applicable				
ECTION 15: Regulate	ory information			
5.1 Safety, health and e	nvironmental regulations/legislation specific for the	substance or mixture		
EU legislation				
Restrictions of occ	upation			
Observe employmen	t restrictions under the Maternity Protection Directive 92	/85/EEC or stricter national regulations, if		
applicable.	applicable.			
	to employment for juvenils according to the 'juvenile wo	k protection guideline' (94/33/EC) or stricter		
-	national regulations, if applicable. Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]			
VOC-value: < 1 g/l		cuvel		
•	C on the limitation of emissions of volatile organic of	ompounds		
	Directive 2004/42/EC on the limitation of emissions of volatile organic compounds VOC limit value 2004/42/IIA(a): 30 g/l (2010)			
	This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.			
-	Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-			
Directive]				
	Named dangerous substances			
•	assified according to Directive 2012/18/EU.			
National regulation	<u>S</u>			
5.2 Chemical Safety As				
-	stances of this mixture a chemical safety assessment h	as been carried out:		
REACH No.	Substance name	CAS No. EC No.		
01-2119475151-45	Calcium dihydroxide	1305-62-0 215-137-3		
ECTION 16: Other in	ormation			
Relevant R-, H- and	EUH-phrases (Number and full text)Relevant R-and	H-phrases (Number and full text):		
H315	Causes skin irritation.	· · · · · · · · · · · · · · · · · · ·		
H318	Causes serious eye damage.			
H335	May cause respiratory irritation			

May cause respiratory irritation.

H335

AURO

420000 ersion 3.1	High-grade lime filler Revision date 08-Jul-2021	Print date 08-Jul-2021
Classification for mixtu	res and used evaluation method according to regulat	tion (EC) No 1272/2008 [CLP]
Eye Dam. 1	Calculation method.	
STOT SE 3 Irritation to	Calculation method.	
respiratory tract Skin Irrit. 2	Calculation method.	
Abbreviations and acro	-	and has Deed
OEL: Occupational Expo	ent concerning the International Carriage of Dangerous G	loods by Road
BLV: Biological limit value		
CAS: Chemical Abstracts		
CLP: Classification, Labe		
CMR: Carcinogenic, Mut		
	Standardization / German industrial standard	
DNEL: Derived No-Effect		
EAKV: European Waste	5	
EC: Effective Concentrat EC: European Communit		
EN: European Standard	y	
	Air Transport Association – Dangerous Goods Regulation	ns
	Code for the Construction and Equipment of Ships carryin	
	vil Aviation Organization Technical Instructions for the Sa	
	I Maritime Code for Dangerous Goods	
	zation for Standardization	
LC: Lethal Concentration		
LD: Lethal Dose	a concentration	
MWC: Maximum wokplac	tion: The International Convention for the Prevention of F	Pollution from Shins
	Economic Cooperation and Development	Shadon nom Ships
PBT: persistent, bioaccur		
PNEC: Predicted No Effe		
RID: Regulations concer	ning the International Carriage of Dangerous Goods by Ra	ail
UN: United Nations		
VOC: Volatile Organic Co		
vPvB: very persistent and	I very bioaccumulative	
Indication of changes		
* Data changed compare	d with the previous version	