AURO

	0023 sion 6.0	Natural resin oil stain, Classic, white Revision date 12-Feb-2024 Print date 07-Mar-2					
SE	CTION 1: Identification of	the substance/mixture and of the company/undertaking					
1.1	Product identifier						
	Trade name/designation						
	9300023	Natural resin oil stain, Classic, white					
	UFI:	64V0-30VF-T007-VVP6					
.2	-	the substance or mixture and uses advised against					
	Relevant identified uses	, and the second s					
	Plating agent						
.3	Details of the supplier of the	e safety data sheet					
	Supplier	· · · · · · · · · · · · · · · · · · ·					
	AURO Pflanzenchemie AG						
	Alte Frankfurter Straße 211 A	Telephone: +49 531 28141-0					
	38122 Braunschweig	Telefax: +49 531 28141-72					
	Germany	E-mail: info@auro.de Website: www.auro.de					
	Department responsible for						
	E-mail (competent person)	msds@auro.de					
4	Emergency telephone numb						
	Emergency telephone number						
	Only available during office ho						
SE	CTION 2: Hazards identified	cation					
.1	Classification of the substar	nce or mixture					
		Regulation (EC) No 1272/2008 [CLP]					
	Skin Sens. 1; Skin sensitisation Aquatic Acute 1; Hazardous to	s; H226 Flammable liquid and vapour. on; H317 May cause an allergic skin reaction. o the aquatic environment; H400 Very toxic to aquatic life. s to the aquatic environment; H410 Very toxic to aquatic life with long lasting effects.					
2.2							
		ulation (EC) No. 1272/2008 [CLP]					
	Hazard pictograms						
	GHS02 GHS07 GHS03	9					
	Signal word						
	Warning						
	Hazard statements						
		lammable liquid and vapour.					
		Aay cause an allergic skin reaction.					
		ery toxic to aquatic life with long lasting effects.					
	Precautionary statements P101 If medical advice is needed, have product container or label at hand.						
		Leep out of reach of children.					
		Leep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.					
		toop away norm hoat, not banaboo, opanto, opon namos and banon ignation boarboo. No binoking.					
	P210 K P273 A	void release to the environment.					
	P210 K P273 A P280 W	void release to the environment. Vear protective gloves and eye/face protection.					
	P210 K P273 A P280 W P370 + P378 In	woid release to the environment. Vear protective gloves and eye/face protection. In case of fire: Use extinguishing powder or sand to extinguish.					
	P210 K P273 A P280 W P370 + P378 In P391 C	void release to the environment. Vear protective gloves and eye/face protection.					



9300023	Natural resin oil stain, Classic, white	
Version 6.0	Revision date 12-Feb-2024	Print date 07-Mar-2024

turpentine, oil

Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1-methylethylidene)-cyclohexene and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene

Supplemental hazard information

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH211 2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

Hazardous ingredients

	CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
*	- 939-409-2 -	Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1- methylethylidene)-cyclohexene and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene 01-2119969963-17-xxxx Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Skin Sens. 1B H317 / Aquatic Acute 1 H400 (M = 1,00) / Aquatic Chronic 1 H410 (M = 1,00)	35,0 < 50,0
*	8006-64-2 932-349-8 650-002-00-6	turpentine, oil 01-2119553060-53-0007 Flam. Liq. 3 H226 / Acute Tox. 4 H302 / Asp. Tox. 1 H304 / Acute Tox. 4 H312 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 / Aquatic Chronic 2 H411 ATE (oral): = 3,956 mg/kg ATE (oral): = 3,956 mg/kg	3,00 < 5,00

Remark

Full text of H- and EUH-statements: see section 16.Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media



9300023	Natural resin oil stain, Classic, white
Version 6.0	Revision date 12-Feb-2024

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: refer to section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class LGK3 - Flammable liquids

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No. Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
------------------------	--------	--



30002 ersior	-		in oil stain, Classic, w ate 12-Feb-2024	hite	Print date 07-l	Mar-20
8	3006-64-2	turpentine, oil		WEL	566 / 850 (-) mg/m³	
A	dditional inform	ation				
		erm occupational exposur				
		rm occupational exposur	e limit value			
Biological limit values						
	lo data available Exposure controls	.				
	•		ed with local or room	suction		
Provide good ventilation.This can be achieved with local or room suction. Personal protection equipment						
	-					
Respiratory protection In case of inadequate ventilation wear respiratory protection.						
	land protection					
TI	hickness of the gl	NBR (Nitrile rubber) ove material >= 0.4 mm >= 480 min				
Breakthrough time >= 480 min For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure Recommended glove articles:EN ISO 374						ided by
	kin protection					
		help protecting exposed	skin areas. In no cas	e should they be use	d after contact.	
	ye/face protectio					
		de protection: EN 166				
	Body protection	h ahamiaal ay hatanaaa in	rotoctive elething with	CE lobale including	the four control digite must be worn	
	invironmental ex	-	biotective clothing with		the four control digits must be worn.	
		er into surface water or d	rains			
		al and chemical prop				
1 In	nformation on ba	sic physical and chemi	cal properties			
Р	Physical state		Liquid			
С	Colour		refer to label			
0	Ddour		characteristic	>		
p	н		not determin	ed		
M	lelting point/freezi	ing point	not determin	ed		
	nitial boiling point		not determin			
	lash point	3 3 3	53 °C			
	ammability			quid and vapour.		
	ower explosion lin	nit at 20°C	not determin			
	Jpper explosion lin		not determin			
				eu		
	/apour pressure a		2.601 mbar	•		
	Relative vapour de	nsity	not applicabl	е		
	Density at 20 °C		1.0 kg/l			
	Vater solubility at		practically in			
	Partition coefficient		see section ?			
lg	gnition temperatur	re in °C	not determin	ed		
D	Decomposition terr	nperature	not determin	ed		
	/iscosity at 20 °C:		< 220 mm²/s			
V	,					
	Other information	I				



9300023	Natural resin oil stain, Classic, white
Version 6.0	Revision date 12-Feb-2024

Print date 07-Mar-2024

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

* Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO2), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

turpentine, oil

LD50: oral (Rat): = 3,956 mg/kg

* LD50: oral (Rat): = 3,956 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

* Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Acute (short-term) fish toxicity



9300 Vers	023 ion 6.0	Natural resin oil stain, Classic, white Revision date 12-Feb-2024 Print date 07-Mar-2024		
*	Reaction mass of 1-Methyl- methyl-4-(propan-2-yl)cyclo LC50: (Danio rerio (zebrafish			
*	Acute (short-term) toxicity ErC50: (Desmodesmus subs			
*	Acute (short-term) toxicity EC50 (Daphnia magna (Big v			
12.2	Persistence and degradabi No information available.	ity		
12.3	Bioaccumulative potential			
*	Partition coefficient: n-octano methylethylidene)-cyclohexer	/water = 4.88 (Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4-(1- e and 1-methyl-4-(propan-2-yl)cyclohexa-1,3-diene)		
12.4	Mobility in soil			
	No information available.			
12.5	Results of PBT and vPvB a	sessment		
	The substances in the mixtur	e do not meet the PBT/vPvB criteria according to REACH, annex XIII.		
12.6'	* Endocrine disrupting prope	rties		
	No information available.			
12.7	Other adverse effects			
	No information available.			
SE	CTION 13: Disposal cons	derations		
13.1	Waste treatment methods			
	Product/Packaging disposa			
	Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/ EC, covering waste and dangerous waste.			
	Waste codes/waste design	tions according to EWC/AVV		
	080111* - Waste paint and va	rnish containing organic solvents or other dangerous substances		
	Other disposal recommend	ations		
	Non-contaminated packages	may be recycled. Vessels not properly emptied are special waste.		
SE	CTION 14: Transport info	mation		
14.1	UN number or ID number			
	UN 1263			
14.2	UN proper shipping name			
	Land transport (ADR/RID)			
	Paint			
	Sea transport (IMDG)			
	Paint			
	Air transport (ICAO-TI / IAT	A-DGR)		
	Paint			
14.3	Transport hazard class(es)			
	Land transport (ADR/RID)	3		
	Sea transport (IMDG) Air transport (ICAO-TI / IATA	3 DGR) 3		
14 4	Packing group	Der() 5		
14.4	Land transport (ADR/RID)			
	Sea transport (IMDG)			
	Air transport (ICAO-TI / IATA	DGR) III		
14.5	Environmental hazards			
	Land transport (ADR/RID) Sea transport (IMDG)	ENVIRONMENTALLY HAZARDOUS Marine pollutant		
14.6	Special precautions for use	r		
*	Transport always in closed, u	oright and safe containers. Make sure that persons transporting the product know what to do in case		



9300023 Version 6.0 Natural resin oil stain, Classic, white Revision date 12-Feb-2024

of an accident or leakage. Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

- Tunnel restriction code: D/E
- Limited quantity (LQ): 5 ltr Hazard identification number (Kemler No.): 30

Sea transport (IMDG)

EmS-No.: F-E, S-E Limited quantity (LQ): 5 ltr

> Air transport (ICAO-TI / IATA-DGR) not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

* Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

* VOC value: 414 g/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

- * VOC limit value: 2004/42/IIA(e): 400 g/l (2010)
- Maximum VOC content of the product in a ready to use condition: 414

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Hazard categories / Named dangerous substances

E1 Hazardous to the aquatic environment in Category Acute 1 or Chronic 1

- Quantity 1: 100t; Quantity 2: 200t P5c FLAMMABLE LIQUIDS
- Quantity 1: 5,000t; Quantity 2: 50,000t

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

	REACH No.	Substance name	CAS No. EC No.
*	01-2119969963-17-xxxx	Reaction mass of 1-Methyl-4-(1-methylethenyl)cyclohexene and 1-Methyl-4- (1-methylethylidene)-cyclohexene and 1-methyl-4-(propan-2- yl)cyclohexa-1,3-diene	- 939-409-2
*	01-2119553060-53-0007		8006-64-2 932-349-8

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.



Version 6.0	Natural resin oil stain, Classic, white Revision date 12-Feb-2024	Print date 07-Mar-2024
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
Classification for mix	tures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]
Flam. Liq. 3	On basis of test data.	,
Skin Sens. 1	Calculation method.	
Aquatic Acute 1	Calculation method.	
Aquatic Chronic 1	Calculation method.	
Abbreviations and ac	ronyms	
OEL: Occupational Ex BLV: Biological limit va CAS: Chemical Abstra CLP: Classification, La CMR: Carcinogenic, M DIN: German Institute DNEL: Derived No-Effe EAKV: European Was EC: Effective Concent EC: European Commu EN: European Standal IATA-DGR: Internation IBC Code: International ICAO-TI: International IMDG Code: International ISO: International Orga LC: Lethal Concentrati LD: Lethal Dose MWC: Maximum wokp MARPOL: Maritime Po OECD: Organisation fo PBT: persistent, bioac PNEC: Predicted No E	Ilues cts Service belling and Packaging utagenic and Reprotoxic for Standardization / German industrial standard act Level te Catalogue Directive ration nity d al Air Transport Association – Dangerous Goods Regulations Il Code for the Construction and Equipment of Ships carrying Dange Civil Aviation Organization Technical Instructions for the Safe Trans nal Maritime Code for Dangerous Goods anization for Standardization on lace concentration Ilution: The International Convention for the Prevention of Pollution for comulative, toxic ffect Concentration erning the International Carriage of Dangerous Goods by Rail	erous Chemicals in Bulk sport of Dangerous Goods by Air

* Data changed compared with the previous version.